

Wireless Collaboration. Connect. Teach. Share.





vivitek[.] **Novo**Connect

Easy to connect, easy to use, easy to enjoy!

For today's students, a blackboard just isn't enough. Social media, videos and other online resources play a vital part in the educational experience. NovoConnect Solution enables students to contribute to the classroom, while keeping educators and administrators in full control of content.





Connect

Connect to share content and mirror any device directly onto the big screen at meetings and lectures.



Teach

Work with up to 64 participants, sharing screens from up to 4 devices with cross-platform screen mirroring.



Share

Share ideas and files instantly with all participants, so no one is out of the loop.

No time to waste

Teachers have no time to waste fumbling around with cables. That's where NovoConnect comes in – full wireless operation and support for content sharing enable educators to make the most out of every lesson.



Keep in control

NovoConnect's innovative moderator preview function enables students participate fluidly in the discussion, all while giving the teacher full control over displayed content - so there are no surprises.



No license fee

Free software upgrades and no license fee enable large scale implementation with no hidden costs.



Bring your own device

NovoConnect is a wireless presentation system designed for the education market and based on the BYOD principle. That means that everyone can connect and share content using the Windows, Mac, Android, iOS or Chromebook device of their choice.





vivitek[.] **Novo**Connect

Connect, engage, learn!

SETUP

connection


 $\overline{\mathbb{P}}$

BYOD

mirroring function.

Getting started with a QR code scan.

Quick



4 Split Screen



vívitek[.] NovoConnect

Specifications









	NovoTouch LK6530i	NovoTouch LK7530i	NovoTouch LK8630i	NovoTouch LK9810i	
Display Technology	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)	
Panel Size; Aspect Ratio	65", 16:9	75", 16:9	86", 16:9	98", 16:9	
Brightness	350cd/m ²	330cd/m ²	330cd/m ²	440cd/m ²	
Contrast Ratio (Typical)	1,200:1	1,200:1	1,200:1	1,300:1	
Native Resolution	4K Ultra-HD (3840 x 2160)				
Viewing Angle (Horiz/ Vert)	178°/178°				
Refresh Rate (Hz)	60Hz	60Hz	60Hz	60Hz	
Display Color (Bit)	1.06 billion (10-bit)				
Orientation	Landscape				
Touch Technology	Infrared Touch				
Touch Points	10 Writing, 20 Touch	10 Writing, 20 Touch	10 Writing, 20 Touch	5 Writing, 20 Touch	
Surface Protection	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)				
Minimum Touch Object	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm				
Touch Tools	Finger, Stylus, Glove, Opaque Objects				
Gestures Supported	Yes				
System Version	Android™ v6.0	Android™ v6.0	Android™ v6.0	Android™ v4.2.1	
СРИ	RK3399, Dual-Core ARM® Cortex® A72 and Quad Core ARM® Cortex® A53 Cortex® A9 Dual Core CPU				
GPU	Mali™ T860	Mali™ T860	Mali™ T860	Quad Core GPU	
RAM	4GB DDR3	4GB DDR3	4GB DDR3	1.5G RAM	
Internal Storage	16GB	16GB	16GB	8GB	
OS Compatibility	Windows® (Windows 7 and above: Driver Free), Mac® (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernal v3.5 and above)				
I/O Ports	HDMI v1.4 (x1), HDMI v1.3 (x3), AV-In (x1), vGA-In (x1), Audio-In (3.5mm) (x1), AV-In (x1), HDMI-Out (1080P) (x1), Audio-Out (3.5mm) (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB Type A 3.0 (x2), USB Type B (x2) HDMI v1.4 (x1), HDMI v1.3 (x3), AV-In (x1), VGA-In (x1), Audio-Out (3.5mm (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4) USB 3.0 (x1), USB Type B (x2)				
Internal Speakers	12W (x2) (Stereo)	12W (x2) (Stereo)	12W (x2) (Stereo)	10W (x2) (Stereo)	
Power Supply (Internal)	AC 100-240V, 50/60Hz				
Dimensions	1,521 x 915 x 99 mm	1,762 x 1,034 x 101 mm	1,988 x 1,178 x 99.6 mm	2,257 x 1,335 x 121 mm	
Weight (Net)	46 kg	60 kg	107 kg	150 kg	
Accessories (Standard)	AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control, Wall Mount Kit,				

Accessories (Standard) Documentation Kit

		· · · · · · · · · · · · · · · · · · ·			
	NovoCast	NovoPro	NovoEnterprise		
Model	NC1000	NP2000	NE3000EU		
Support Operating System	Windows 7 / 8 / 10 (32 bits and 64 bits), macOS 10.7 and above, iOS 7.0 and above, Android 4.0 and above				
Desktop Streaming	up to 1080p, 60 fps				
Mobile Screen Mirroring	Google cast for Android; AirPlay for iOS				
Usage Mode	Education mode	Corporate mode;	Education mode		
Max. Participants	Up to 8 Up to 64				
Split Screen	Up to 4				
WiFi	802.11b/g/n 2.4GHz, 1T1R with 1 external antenna	802.11ac, b/g/n 2.4GHz & 5GHz, 2T2R	802.11ac, b/g/n, 2.4GHz & 5GH 2T2R with 2 external antenna		
Output	HDMI-Out; Audio-Out 3.5mm mini jack	HDMI-Out	HDMI-Out; Audio-Out 3.5mm mini jack		
Output Resolution	FullHD1080p (1920 x 1080); WXGA (1280 x 800); HD720p (1280 x 720); XGA (1024 x 768)				
Input	USB Type A; MicroSD Slot; DC Jack Power-In; Optional Ethernet RJ45 Adaptor	Ethernet RJ45; USB Type A; MicroSD Slot; MicroUSB Power-In	Ethernet RJ45 (PoE); USB Type A x 2; MicroSD Slot; HDMI-In; Audio-In 3.5mm mini jack; DC Jack Power-In		
CPU	ARM Cortex A9 Quad-Core at 1.6 GHz				
Storage	8GB				
Security	Dual Network WiFi & LAN; AES-128 encryption; Kensington lock				
Power	Input to AC adaptor: AC 100-240V, 50/60Hz. Output from AC adaptor: 5V/2A. Consumption: 10W				
Dimensions (L x W x H)	100 x 100 x 20 mm	120 x 75 x 16 mm	165 x 123 x 21 mm		
Weight	184 g	128 g	250 g		

	Launcher Plus
Model	QL300
Support Operating System	Windows 7 / 8 / 10 (32 bits and 64 macOS 10.7 and above
WiFi	embedded WiFi
Dimensions (L x W x H)	70 x 70 x 14 mm
Weight	60 g





GHz, nae

64 bits),





CONTACT US

Vivitek EMEA Headquarters Zandsteen 15 2132 MZ Hoofddorp The Netherlands Tel: +31 20-8003960 www.vivitek.eu

www.novoconnect.eu

