

Model Name	NovoTouch LK6530i	NovoTouch LK7530i	NovoTouch LK8630i	NovoTouch LK9820i
<b>Display Technology</b>	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)	Backlit LED (IPS Panel)
<b>Panel Size; Aspect Ratio</b>	65", 16:9	75", 16:9	86", 16:9	98", 16:9
<b>Brightness</b>	350cd/m <sup>2</sup>	350cd/m <sup>2</sup>	350cd/m <sup>2</sup>	500cd/m <sup>2</sup>
<b>Contrast Ratio (Typical)</b>	1,200:1	1,200:1	1,200:1	1,300:1
<b>Native Resolution</b>	4K Ultra-HD (3840 x 2160)			
<b>Viewing Angle (Horiz/Vert)</b>	178°/178°			
<b>Refresh Rate (Hz)</b>	60Hz	60Hz	60Hz	120Hz
<b>Display Color (Bit)</b>	1.06 billion (10-bit)			
<b>Orientation</b>	Landscape			
<b>Touch Technology</b>	Infrared Touch			
<b>Touch Points</b>	10 Writing, 20 Touch	10 Writing, 20 Touch	10 Writing, 20 Touch	10 Writing, 10 Touch
<b>Surface Protection</b>	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)			
<b>Minimum Touch Object</b>	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm			
<b>Touch Tools</b>	Finger, Stylus, Glove, Opaque Objects			
<b>Gestures Supported</b>	Yes			
<b>System Version</b>	Android™ v6.0	Android™ v6.0	Android™ v6.0	Android™ v5.0
<b>CPU</b>	RK3399, Dual-Core ARM® Cortex® A72 and Quad Core ARM® Cortex® A53			Quad Core ARM Cortex A53 CPU - Up to 1.4GHz
<b>GPU</b>	Mali™ T860	Mali™ T860	Mali™ T860	Mali™- 450
<b>RAM</b>	4GB DDR3	4GB DDR3	4GB DDR3	2GB DDR3
<b>Internal Storage</b>	16GB	16GB	16GB	16GB
<b>OS Compatibility</b>	Windows® (Windows 7 and above: Driver Free), macOS (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernal v3.5 and above)			
<b>I/O Ports</b>	HDMI v2 (x1), HDMI v1.4 (x2), DisplayPort (x1), VGA-In (x1), Audio-In (3.5mm) (x1), AV-In (x1), HDMI-Out (1080P) (x1), Audio-Out (3.5mm) (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB Type A 3.0 (x2), USB Type B (x2)			HDMI v2 (x4), HDMI v1.4 (x1), VGA-In (x1), YPbPr-In (x1), AV-In (x1), Audio-In 3.5mm (x1), Microphone-In 3.5mm (x1), HDMI-Out v2.0 (4K-UHD) (x1), AV-Out (x1), , Audio-Out 3.5mm (x1), LAN (x1), RS232 (x1), USB A 2.0 (x4), USB A 3.0 (x2), USB B for Touch (x2)
<b>Internal Speakers</b>	12W (x2) (Stereo)	12W (x2) (Stereo)	12W (x2) (Stereo)	15W (x2) (Stereo)
<b>Power Supply</b>	AC 100-240V, 50/60Hz			AC 100-240V, 50/60Hz. Consumption: 480W, <0.5W (Standby)
<b>Panel Dimensions</b>	1,521 x 915 x 99 mm	1,762 x 1,034 x 101 mm	1,988 x 1,178 x 99.6 mm	2242 x 1338 x 117 mm
<b>Panel Weight (Net)</b>	46 kg	60 kg	107 kg	138 kg
<b>What's included</b>	Touch Screen Panel, NovoConnect Solution Module VKA05, Wall Mount WIB9060A, Documentation Kit, AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control with Batteries.			Touch Screen Panel, NovoEnterprise NE3000EU, Wall Mount, Documentation Kit, AC Power Cord, HDMI Cable, USB Cable, Audio Cable, Stylus (x2), Remote Control with Batteries.
<b>Options</b>	NovoConnect Solution LauncherPlus QL300EU, NovoTouch Plug-In Windows OPS Module VKW21			NovoConnect Solution LauncherPlus QL300EU
<b>Model UPC Code</b>	813097023063	813097023056	813097023049	813097024329
<b>Warranty</b>	3 years RTB			